



## Velocity-Controlled Piezoelectric Switching Energy Harvesting Device

Yuan-Ping Liu<sup>1,2</sup>, Dejan Vasic<sup>1</sup>, François Costa<sup>1,3</sup>, Wen-Jong Wu<sup>2,\*</sup>, C. K. Lee<sup>2,4,5</sup>

<sup>1</sup>Système et Application des Technologies de l'Information et de l'Energie, UNIVERSud, Ecole Normale Supérieure de Cachan, France

<sup>2</sup>Department of Engineering Science and Ocean Engineering, National Taiwan University, Taipei, Taiwan

<sup>3</sup>IUFM de Créteil, Université Paris 12, Place du 8 mai 1945, 93000 St Denis, France

<sup>4</sup>Institute of Applied Mechanics, National Taiwan University, Taiwan

<sup>5</sup>Industrial Technology Research Institute of Taiwan, Taiwan

Address: No.1, Sec. 4, Roosevelt Rd., Da-an District, Taipei City 106, Taiwan

Phone/Fax number: +886 2 3366 5764, e-mail: ypliu@mems.iam.ntu.edu.tw

### Abstract

The main purpose of this paper is to design the interface circuit of the piezoelectric energy harvesting device which can be suitable for a resistive load or a capacitive load. The vibrating velocity is detected to control the active rectifier to make the power factor correction of the piezoelectric layers. However, there are switching losses in the active rectifier in practice. The dead time and an inductor are thus taken into consideration to minimum the switching loss. The proposed circuit can increase 4 times than typical interface circuit of the piezoelectric layer, and can increase the charging speed of the capacitive storage buffer as well.

### Key words

Piezoelectric layers, power factor correction, power harvesting, capacitive storage

### References

- [1] D. Guyomar, A. Badel, E. Lefeuvre and C. Richard, "Toward Energy Harvesting Using Active Materials and Conversion Improvement by Nonlinear Processing", *IEEE Trans. Ultrason. Ferroelectr. Freq. Control*, Vol. 52, pp. 584–595, 2005.
- [2] E. Lefeuvre, A. Badel, C. Richard and D. Guyomar, "Piezoelectric Energy Harvesting Device Optimization by Synchronous Electric Charge Extraction", *J. Intell. Mater. Syst. Struct.*, Vol. 16 pp. 865–876, 2005.
- [3] W. J. Wu, A. Wickenheiser, T. Reissman, and E. Garcia, "Modeling and Experimental Verification of Synchronized Discharging Techniques for Boosting Power Harvesting from Piezoelectric Transducers", *Smart Materials and Structures* (accepted).
- [4] Y. P. Liu, D. Vasic, F. Costa, W. J. Wu, C. K. Lee, "Velocity-Controlled Switching Piezoelectric Damping Based on Maximum Power Factor Tracking and Work Cycle Observation", *Proceedings of 19th International Conference on Adaptive Structures and Technologies (ICAST 2008)*, paper no. 40, Ascona, Switzerland, October 6-9, 2008.